

Olah Technologies LLC

194 Asheberne Dr.
Washington NC, 27889

AirBoss Operators Manual

READ CAREFULLY BEFORE OPERATING THIS DEVICE

INDEX

LEGAL DISCLAIMER.....3

SOME BASIC SAFETY RULES.....4

OPERATING THE AIR BOSS.....5

LEGAL DISCLAIMER

WARNING, SERIOUS INJURY OR DEATH CAN RESULT IF THIS PRODUCT IS MISUSED

The Pamlico County Sheriff has determined that the Air Boss is legal in his jurisdiction and has contacted the Bureau of Alcohol, Tobacco and Firearms (BATF). BATF advised that it is not considered a firearm since it does not use an explosive propellant and the muzzle velocity is well below 400ft/sec.

Other United States jurisdictions or OTHER COUNTRIES may have laws or local ordinances prohibiting the use of this device. It is your responsibility to ensure that its use complies with local requirements.

DO NOT Overfill this product with compressed air. Overfilling is defined as any pressure exceeding 75 psi and any pressure causing the product to explode. Death or serious injury can also occur if the product is dropped on a sharp object while filled with any amount of pressure. Death or Serious injury from this product can occur if the user performs unsafe acts with the AirBoss. Unsafe acts are any actions that could cause death or harm to the operator or other living beings. DO NOT use this product around power lines. Purchase and use of this product is at the buyer's own risk. This is your formal notification of disclosure; the seller cannot be held liable for ANYTHING the buyer uses this product for. Also, this product is NOT legally considered a firearm and was verified by Pamlico County NC Sheriff's office.

SOME BASIC SAFETY RULES

1. This device uses a tethered 2oz lead fishing sinker propelled at high speeds.
2. Always be sure the barrel is clear of any obstruction.
3. Always use eye protection.
4. Never aim or discharge this device in the direction of anyone.
5. Be sure that the landing area is clear of people or animals.
6. Never use this device near any power lines.
7. Never leave or store the device while pressurized.
8. Always attach the reel of choice BELOW the barrel of the launcher. This will ensure that if the sinker rebounds because of a snag or failure to open the bail, it will return the sinker below your face.

USING THE AIR BOSS

Start with the valve closed.

For most applications, to clear an 80ft tree it will require 45 to 50psi. Using a suitable hand or powered pump, put air in the chamber until the pressure gauge reads 50psi.

DO NOT EXCEED 75 PSI

-Be sure the sinker is firmly tied to the nylon line. Place the sinker in the barrel of the Air Boss and open the bail on the reel. Raise the barrel of the Air Boss to allow the sinker to fall to the valve.

-BE SURE TO OPEN THE BAIL BEFORE FIRING THE DEVICE AND WEAR YOUR EYE PROTECTION.

-Aim the launcher over the tree you wish to put the antenna in and open the valve quickly.

-After the shot, keep the launcher pointed up until the sinker falls to the ground. Once the sinker has landed, give the reel a few turns to close the bail and take up slack. Place the launcher on the ground.

-Locate the sinker and remove it from the nylon line. Attach the rope you wish to use to pull up the antenna with. Return to the launcher and reel the new rope over the tree. Do not attempt to pull the sinker back over the tree. It will most certainly wrap around a branch and be there for years.

Once the rope is in place, use it to raise the antenna.